

E-Style Hose Specifications

ITEM NO	SIZE (INCH)	OD OF HOSE MM	ID OF HOSE MM	BEND RADIUS STATIC MM	BEND RADIUS DYNAMIC MM	MAX W.P.R (WITH SINGLE BRAID) PSI	BURST PRESS. (WITH SINGLE BRAID) PSI	MAX W.P.R. (WITH DOUBLE BRAID) PSI	BURST PRESS. (WITH DOUBLE BRAID) PSI
1	1/4	12.2 ± 0.25	7.9 ± 0.25	25	100	2234	8934	3568	14272
2	3/8	15.8 ± 0.25	10.5 ± 0.25	40	150	1523	6092	2437	9747
3	1/2	17.5 ± 0.50	12.5 ± 0.50	50	200	1276	5105	2031	8122
4	5/8	22.5 ± 0.50	16.5 ± 0.50	50	200	1059	4235	1682	6730
5	3/4	25.5 ± 0.50	18.7 ± 0.50	70	200	928	3713	1479	5918
6	1	35.0 ± 0.50	25.50 ± 0.50	90	200	725	2901	1160	4641
7	1-1/4	42.0 ± 0.50	32.50 ± 0.50	110	250	609	2437	972	3887
8	1-1/2	52.0 ± 0.50	40.40 ± 0.50	130	250	464	1856	740	2959
9	2	65.0 ± 0.50	50.60 ± 0.50	175	350	450	1798	711	2843
10	2-1/2	81.0 ± 0.50	65.60 ± 0.50	200	410	377	1508	595	2379
11	3	95.0 ± 0.50	80.20 ± 0.50	205	450	261	1044	406	1624
12	4	117.0 ± 0.50	100.90 ± 0.50	230	560	232	928	377	1508
13	5	145.0 ± 0.50	125.60 ± 0.50	280	660	232	928	363	1450
14	6	175.0 ± 0.50	150.80 ± 0.50	320	815	203	812	319	1276
15	8	228.0 ± 0.50	198.40 ± 0.50	435	1015	145	580	232	928

TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE