

P-Style Specifications

ITEM NO	SIZE (INCH)	OD OF HOSE MM	ID OF HOSE MM	BEND RADIUS STATIC MM	BEND RADIUS DYNAMIC MM	MAX. W.P.R. (WITH SINGLE BRAID) PSI	BURST PRESS. (WITH SINGLE BRAID) PSI	MAX. W.P.R. (WITH DOUBLE BRAID) PSI	BURST PRESS. (WITH DOUBLE BRAID) PSI
1	3/8	16.5± 0.25	9± 0.25	45	140	1087	5727	1522	8990
2	1/2	22± 0.50	12± 0.50	60	185	1087	5655	1522	8700
3	5/8	25± 0.50	16± 0.50	70	195	942	3915	1305	6670
4	3/4	30± 0.50	19± 0.50	75	200	681	3262	1015	5800
5	1	38± 0.50	25± 0.50	85	215	551	2320	797	4422
6	1-1/4	46± 0.50	32± 0.50	115	230	493	2320	696	3915
7	1-1/2	54± 0.50	38± 0.50	140	280	435	2320	594	3915
8	2	69± 0.50	50± 0.50	160	335	362	1740	522	2972
9	2-1/2	84± 0.50	63± 0.50	190	420	304	1595	435	2682
10	3	99± 0.50	76± 0.50	220	500	275	1232	391	2320
11	4	130± 0.50	101± 0.50	340	690	203	928	290	1595
12	5	155± 0.50	126± 0.50	480	1030	145	652	203	1305
13	6	177± 0.50	152± 0.50	750	1325	101	435	174	942

TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE